

R 7227S TC

Paraffin wick heater



Product data sheet

Product category	Product category
Brand	Qlima
Model	R 7227S TC
Colour	Inox
EAN code	8713508778839

Technical specifications

Burner type		Single Burner
Capacity heating	kW	2,70
For rooms up to	m ²	18 - 38
	m ³	45 - 95
Consumption (max.)	l/h	0,281
	g/h	225
Tank capacity	l	4,2
Autonomy	h	15
Batteries required		4 x C (LR14)
Batteries included		No
Dimensions (w x d x h) ¹	mm	455 x 295 x 495
Net. weight	kg	9
Guarantee ²	years	2
Safety features	Tip-over switch - Safety stop - Overheat protection - Safe top - CO ₂ sensor	

¹ including base plate

² except ignition, manual fuel pump, glass cylinder(s) and wick.

Package content

Paraffin wick heater

Accessories (not included)

Description	EAN code

Qlima



Removable fuel tank



Tilt protection



Safety stop



Safe touch top plate



Spark ignition

Features

No installation: This heater can be installed without wires and without exhaust pipes. This makes it a very convenient heating source.

High efficiency: This heater has a 99.99% heat efficiency with infrared radiation heating.

Wick-stop:

The wick stop mechanism of this heater limits the flame height adjustment. This ensures a clean combustion.

Safe top: This heater is equipped with a safe top. The temperature of the top plate is kept relatively low for improved safety.

Safety stop:

This heater is equipped with a shut-off safety switch. By pressing this switch the heater will be shut off immediately.

Room temperature thermistor:

This heater automatically shuts off when the room temperature becomes too high, to avoid the risk of a lack of oxygen.

Battery cover:

This heater is equipped with a cover for the batteries.

Fuel filter:

Protects the burner system.

Manual fuel syphon pump:

This heater is delivered with a convenient pump to fill the fuel tank.

Spark ignition:

This heater is ignited via a state-of-the-art spark ignition system. Due to the high voltage of the spark the heater is ignited very quick. The spark ignition system is very durable and can be used during the whole lifespan of the heater without any maintenance or replacement of parts.
